

ATTESTATION OF CONFORMITY

Issued to: Foshan Eaglerise Power Science & Technology (Shunde)Co.,Ltd.
No.4 East Huanzhen Road, Beijiao, Shunde, Foshan, Guangdong, China

For the product: LED power supply

Trade name: 

Type/Model: see annex

Ratings: see annex

Manufactured by: Foshan Eaglerise Power Science & Technology (Shunde)Co.,Ltd.
No.4 East Huanzhen Road, Beijiao, Shunde, Foshan, Guangdong, China

Requirements: EN IEC 55015:2019 + A11:2020
EN 61547:2009
EN IEC 61000-3-2:2019 + A1:2021
EN 61000-3-3:2013 + A1:2019 + A2:2021

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no 4911168.50.

This Attestation implies that the examined types are in accordance with the standards designated under the Electromagnetic Compatibility Directive (EMC) 2014/30/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

The CE marking may be affixed on the product if all relevant and effective EC directives are complied with.

Arnhem, 5 December 2023

Number: 4911168.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.,
Guangzhou Branch



May Liu
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed



Annex

Document no. : 4911168.01AOC

Type/Model:

No.	Model	Input			Output			
		Voltage	Max.	Frequency	Constant	Normal working	No load working	Max.
		(VAC)	Current(A)	(Hz)	current (mA)	voltage (Vdc)	voltage (Vdc)	Power(W)
Series 1	LS-40-600 LI ADV	220-240	0.17	50/60	600	30-40	59	24
	LS-40-650 LI ADV	220-240	0.19	50/60	650			26
	LS-40-700 LI ADV	220-240	0.2	50/60	700			28
	LS-40-750 LI ADV	220-240	0.22	50/60	750			30
	LS-40-800 LI ADV	220-240	0.23	50/60	800			32
	LS-40-850 LI ADV	220-240	0.25	50/60	850			34
	LS-40-900 LI ADV	220-240	0.26	50/60	900			36
	LS-40-950 LI ADV	220-240	0.27	50/60	950			38
	LS-40-1000 LI ADV	220-240	0.27	50/60	1000			40
	LS-40-1050 LI ADV	220-240	0.29	50/60	1050	30-38.5	40.4	
Series 2	LS-40-600 LI1 EXC	220-240	0.16	50/60	600	9-42	59	25.2
	LS-40-650 LI1 EXC	220-240	0.18	50/60	650			27.3
	LS-40-700 LI1 EXC	220-240	0.19	50/60	700			29.4
	LS-40-750 LI1 EXC	220-240	0.2	50/60	750			31.5
	LS-40-800 LI1 EXC	220-240	0.22	50/60	800			33.6
	LS-40-850 LI1 EXC	220-240	0.23	50/60	850			35.7
	LS-40-900 LI1 EXC	220-240	0.24	50/60	900			37.8
	LS-40-950 LI1 EXC	220-240	0.25	50/60	950			39.9
	LS-40-1000 LI1 EXC	220-240	0.25	50/60	1000			9-40
	LS-40-1050 LI1 EXC	220-240	0.27	50/60	1050	9-38.5	40.4	
Series 3	LS-40-600 LI1-G EXC	220-240	0.16	50/60	600	9-42	59	25.2
	LS-40-650 LI1-G EXC	220-240	0.18	50/60	650			27.3
	LS-40-700 LI1-G EXC	220-240	0.19	50/60	700			29.4
	LS-40-750 LI1-G EXC	220-240	0.2	50/60	750			31.5
	LS-40-800 LI1-G EXC	220-240	0.22	50/60	800			33.6

	LS-40-850 LI1-G EXC	220-240	0.23	50/60	850			35.7
	LS-40-900 LI1-G EXC	220-240	0.24	50/60	900			37.8
	LS-40-950 LI1-G EXC	220-240	0.25	50/60	950			39.9
	LS-40-1000 LI1-G EXC	220-240	0.25	50/60	1000	9-40		40
	LS-40-1050 LI1-G EXC	220-240	0.27	50/60	1050	9-38.5		40.4
Series 4	LS-40-600 LI EXC S	220-240	0.17	50/60	600	24-42	59	25.2
	LS-40-650 LI EXC S	220-240	0.19	50/60	650			27.3
	LS-40-700 LI EXC S	220-240	0.2	50/60	700			29.4
	LS-40-750 LI EXC S	220-240	0.22	50/60	750			31.5
	LS-40-800 LI EXC S	220-240	0.23	50/60	800			33.6
	LS-40-850 LI EXC S	220-240	0.25	50/60	850			35.7
	LS-40-900 LI EXC S	220-240	0.26	50/60	900			37.8
	LS-40-950 LI EXC S	220-240	0.27	50/60	950			39.9
	LS-40-1000 LI EXC S	220-240	0.27	50/60	1000			24-40
	LS-40-1050 LI EXC S	220-240	0.29	50/60	1050	24-38.5	40.4	

End